

Starlet[®]

upholstery fabric

Specifications



Fiber: 100% Polyester
 Weight: 11.3 oz. per linear yard (± 1 oz.)
 Width: 54 inches
 Backing: Acrylic
 Repeat: 1 3/4" Horizontal x 2 1/8" Vertical

Pattern Direction: Suitable for railroading 

Fabric Performance Symbols indicate that a fabric performs to commercial furniture manufacturing standards and passes all applicable testing as specified by the Association for Contract Textiles (ACT).

Performance

 Abrasion (ASTM-D-4157): 50,000 Double Rubs
 Lightfastness (AATCC-16E): 40 Hours, Class 5
 Colorfastness (AATCC-8): Wet - Class 4.5 Dry - Class 4.5
 Seam Slippage (ASTM-4034): Warp - 94 lbs. Fill - 64 lbs.


 Flame Resistance: California Technical Bulletin 117, Section E
 CS-191-53, Class 1
 BIFMA X5.7-1991
 NFPA 260-1989, Class 1
 UFAC, Class 1
 B.S. 5852 Part 1: 1979 Ignition Source 0; Smoldering Cigarette 

Cleaning Code: WS - For water based stains, use water based cleaning agents.
 For oil based stains, use solvent cleaner.

tissus pour siège





Spécifications



Fibre: 100% Polyester
 Poids: 348 g/m linéaire (± 28 g)
 (11.3 on/verge linéaire ± 1 on)
 Larguer: 137/140cm (54")
 Endos: Acrylique
 Rapport: 4.4 cm Horizontal x 5.4 cm Vertical

Sens du motif: Peut être utilisé à contresens 

Les Symboles de rendement du tissu indiquent que le rendement d'un tissu donné correspond aux normes en matière de mobilier de bureau et a réussi tous les essais précisés par l'Association for Contract Textiles (ACT).

Performance

 Résistance à l'abrasion (ASTM-D-4157): 50,000 Double Cycles
 Solidité de la couleur à la lumière (AATCC-16E): 40 Heures, Classe 5
 Solidité de la couleur au frottement (AATCC-8): Humide - Classe 4.5 Sec - Classe 4.5
 Glissement de la couture (ASTM-4034): Châine - 94 lbs. Trame - 64 lbs.


 Inflammabilité: Bulletin Technique de la Californie 117, Sec. E
 CS-191-53, Classe 1
 BIFMA X5.7-1991
 NFPA 260-1989, Classe 1
 UFAC, Classe 1
 B.S. 5852 Part 1: 1979 Ignition Source 0; Smoldering Cigarette 

Nettoyage: WS - Pour taches a base d'eau utiliser un produit de nettoyage a base d'eau.
 Pour taches a base d'huile utiliser un produit de nettoyage avec solvant.

telas de tapicería





Especificaciones



Fibra: 100% Poliéster
 Peso: 348 g/m lineal (± 28 g)
 Ancho: 137/140cm (54")
 Backing: Acrílico
 Repitir: 4.4 cm Horizontal x 5.4 cm Vertical

Dirección de Diseño: Se puede usar de un lado 

Los símbolos de tapicería de ejecución indican que la tapicería funciona en la factura comercial del mobiliario por las reglas establecidas y pasan todos los reglamentos específicos de la Asociación de Contrato Textil (ACT).

Funcionamiento

 Resistancia a la abrasion (ASTM-D-4157): 50,000 Roces Dobles
 Resistancia a la luz (AATCC-16E): 40 Horas, Classe 5
 Resistancia del color (AATCC-8): Humeda - Classe 4.5 Seca - Classe 4.5
 Fuerza de la costura (ASTM-4034): Urdido - 94 lbs. Trama - 64 lbs.

 Resistancia al Fuego: California Technical Bulletin 117, Section E
 CS-191-53, Classe 1
 BIFMA X5.7-1991
 NFPA 260-1989, Classe 1
 UFAC, Classe 1
 B.S. 5852 Part 1: 1979 Ignition Source 0; Smoldering Cigarette 


Limpieza: WS - Para manchas a base de agua usar limpiadores a base de agua.
 Para manchas a base de aciete usar limpiadores soventes.

SUGGESTED APPLICATIONS FOR THIS PATTERN ARE:



FABRICS BY ABSECON MILLS, INC. • 5/2007

*** Starlet is covered by a 5 year limited performance warranty. Contact your sales representative for written warranty terms and conditions.**



WOVEN WITH WIND POWER